

Ser. No.10/534,965
Amdt. dated July 20, 2008
Reply to Office Action of May 2, 2008

PU020454

RECEIVED
CENTRAL FAX CENTER

JUN 09 2008

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims

1. (Currently Amended) A method for controlling an apparatus having an emergency alert function, comprising:
 - detecting a condition indicating relocation of said apparatus after a power interruption to said apparatus; and
 - enabling a predetermined output associated with said emergency alert function responsive to detecting said condition; and
 - enabling a user to provide updated information associated with the emergency alert function responsive to detecting said condition.
2. (Canceled)
3. (Previously Presented) The method of claim 2, wherein said updated information includes a FIPS location code.
4. (Previously Presented) The method of claim 2, wherein said updated information includes a type of emergency event.
5. (Previously Presented) The method of claim 1, wherein detecting said condition includes detecting a duration of said power interruption.
6. (Previously Presented) The method of claim 5, wherein said condition is detected if said duration exceeds a predetermined time period.
7. (Previously Presented) The method of claim 5, wherein said duration is detected using a vertical blanking interval of a television signal.

PU020454

Ser. No.10/534.965
Amdt. dated July 20, 2008
Reply to Office Action of May 2, 2008

8. (Previously Presented) The method of claim 5, wherein detecting said condition further includes detecting signal strength on a previously identified frequency channel associated with said emergency alert function.

RECEIVED
CENTRAL FAX CENTER

JUN 09 2008

9. (Previously Presented) The method of claim 1, wherein detecting said condition includes detecting signal strength on a first previously identified frequency channel associated with said emergency alert function.

10. (Previously Presented) The method of claim 9, wherein:
said first previously identified frequency channel has previously exhibited higher signal strength relative to a second previously identified frequency channel associated with said emergency alert function; and
said condition is detected if said second previously identified frequency channel exhibits higher signal strength relative to said first previously identified frequency channel.

11. (Currently Amended) An apparatus having an emergency alert function, comprising:
tuning means for tuning signals including emergency alert signals capable of activating said emergency alert function; and
processing means for:
detecting a condition indicating relocation of said apparatus after a power interruption to said apparatus; ~~and for~~
enabling a predetermined output associated with said emergency alert function responsive to detecting said condition; and
enabling a user to provide updated information associated with the emergency alert function responsive to detecting said condition.

12. (Canceled)

13. (Previously Presented) The apparatus of claim 12, wherein said updated information includes a FIPS location code.

Scr. No.10/534,965
Amdt. dated July 20, 2008
Reply to Office Action of May 2, 2008

PU020454

14. (Previously Presented) The apparatus of claim 12, wherein said updated information includes a type of emergency event.
15. (Previously Presented) The apparatus of claim 11, wherein said processing means detects said condition based on a duration of said power interruption.
16. (Previously Presented) The apparatus of claim 15, wherein said processing means detects said condition if said duration exceeds a predetermined time period.
17. (Previously Presented) The apparatus of claim 15, wherein said processing means detects said duration based on a vertical blanking interval of a television signal.
18. (Previously Presented) The apparatus of claim 15, wherein said processing means detects said condition based on signal strength on a previously identified frequency channel associated with said emergency alert function.
19. (Previously Presented) The apparatus of claim 11, wherein said processing means detects said condition based on signal strength on a first previously identified frequency channel associated with said emergency alert function.
20. (Previously Presented) The apparatus of claim 19, wherein:
said first previously identified frequency channel has previously exhibited higher signal strength relative to a second previously identified frequency channel associated with said emergency alert function; and
said processing means detects said condition if said second previously identified frequency channel exhibits higher signal strength relative to said first previously identified frequency channel.
21. (Currently Amended) A television signal receiver having an emergency alert function, comprising:
a tuner operative to tune signals including emergency alert signals capable of activating said emergency alert function; and

Ser. No.10/534,965
Amdt. dated July 20, 2008
Reply to Office Action of May 2, 2008

PU020454

a processor operative to:
detect a condition indicating relocation of said television signal receiver after a
power interruption to said television signal receiver; ~~and to~~
enable a predetermined output associated with said emergency alert function
responsive to detecting said condition; and
enable a user to provide updated information associated with the emergency alert
function responsive to detecting said condition.

22. (Canceled)

23. (Previously Presented) The television signal receiver of claim 22, wherein said
updated information includes a FIPS location code.

24. (Previously Presented) The television signal receiver of claim 22, wherein said
updated information includes a type of emergency event.

25. (Previously Presented) The television signal receiver of claim 21, wherein said
processor detects said condition based on a duration of said power interruption.

26. (Previously Presented) The television signal receiver of claim 25, wherein said
processor detects said condition if said duration exceeds a predetermined time period.

27. (Previously Presented) The television signal receiver of claim 25, wherein said
processor detects said duration based on a vertical blanking interval of a television signal.

28. (Previously Presented) The television signal receiver of claim 25, wherein said
processor detects said condition based on signal strength on a previously identified
frequency channel associated with said emergency alert function.

29. (Previously Presented) The television signal receiver of claim 21, wherein said
processor detects said condition based on signal strength on a first previously identified
frequency channel associated with said emergency alert function.

Ser. No.10/534,963
Amdt. dated July 20, 2008
Reply to Office Action of May 2, 2008

PU020454

30. (Previously Presented) The television signal receiver of claim 29, wherein:
said first previously identified frequency channel has previously exhibited higher signal strength relative to a second previously identified frequency channel associated with said emergency alert function; and
said processor detects said condition if said second previously identified frequency channel exhibits higher signal strength relative to said first previously identified frequency channel.